

Enclosures FlexPak6™



COMPACT ENCLOSURE FEATURING OUR HIGH PERFORMANCE GNSS RECEIVER



FUTURE PROOFED SCALABILITY

The FlexPak6 is software upgradable in the field to provide the custom performance required for your application demands. Capable of tracking all present and upcoming Global Navigation Satellite System (GNSS) constellations and satellite signals including GPS L1/L2/L2C/L5, GLONASS L1/L2/L2C, Galileo E1/E5a/E5b/AltBOC and BeiDou B1/B2 signals, the FlexPak6 ensures high performance GNSS positioning now and in the future.

BASE STATION OR ROVER

Compact and lightweight, the FlexPak6 is well suited for rover applications. With its powerful GNSS engine, onboard NTRIP v1.0 and v2.0 client and server support and enhanced connection options including serial, USB, CAN and Ethernet, the FlexPak6 is also ideal for base station operation.

FLEXIBLE CONFIGURATION OPTIONS FOR YOUR APPLICATION

Proven and innovative NovAtel technology combine to achieve the best in GNSS positioning. NovAtel's industry leading Pulse Aperture Correlator (PAC) multipath mitigation technology is standard and ensures the highest quality measurements and positioning. Innovative new technology provides excellent resistance to interference for consistent, accurate and reliable positioning. Configurable options ensure that your positioning and accuracy needs are met at all times. To learn more about how our firmware options can enhance your positioning, please visit www.novatel.com/products/firmware-options.

BENEFITS

- + Innovative OEM6 technology
- + Supports current and future GNSS signals
- + Compact, lightweight and easy to integrate
- + Ideal for low payload UAV and robotics applications

FEATURES

- + Metre to centimetre-level accuracy
- + Auxiliary strobe signals with configurable PPS output
- + Shock resistant
- + Serial, USB, Ethernet and CAN Bus communications
- + NTRIP client and server
- + Wide input voltage range
- + SPAN® INS functionality

If you require more information about our enclosures, visit www.novatel.com/products/gnss-receivers/enclosures/

PERFORMANCE¹

Channel Configuration

120 Channels²

Signal Tracking

GPS L1, L2, L2C, L5
 GLONASS L1, L2, L2C
 Galileo E1, E5a, E5b, AltBOC
 BeiDou³ B1, B2
 SBAS
 QZSS
 L-Band

Horizontal Position Accuracy (RMS)

Single point L1 1.5 m
 Single point L1/L2 1.2 m
 NovAtel CORRECT™
 » SBAS⁴ 60 cm
 » DGPS 40 cm
 » PPP⁵
 TerraStar-L 40 cm
 TerraStar-C 4 cm
 » RTK 1 cm + 1 ppm
 Initial time <10 s
 Initial reliability >99.9%

Maximum Data Rate⁸

Measurements 100 Hz
 Position 100 Hz

Time to First Fix

Cold start⁹ <50 s
 Hot start¹⁰ <35 s

Signal Reacquisition

L1 <0.5 s (typical)
 L2 <1.0 s (typical)

Time Accuracy¹¹ 20 ns RMS

Velocity Accuracy 0.03 m/s RMS

Velocity¹² 515 m/s

PHYSICAL AND ELECTRICAL

Dimensions 147 x 113 x 45 mm

Weight 337 g

Power

Input voltage +6 to +36 VDC
 Power consumption¹³ 1.8 W

Antenna LNA Power Output

Output voltage 5 VDC ±5%
 Maximum current 100 mA

Connectors

Serial DB9
 USB Mini-AB
 Ethernet, CAN, I/O DB-HD15

COMMUNICATION PORTS

1 RS-232 921,600 bps
 1 RS-232 or RS-422 921,600 bps

1 USB port 12 Mbps
 1 CAN port¹⁴ 1 Mbps

1 Ethernet port supporting:
 » 10BaseT/100BaseT networks
 » Direct TCP/IP & UDP connectivity
 » NTRIP (v2.0) client and server

ENVIRONMENTAL

Temperature

Operating -40°C to +75°C
 Storage -40°C to +85°C

Humidity 95% non-condensing

Vibration (operating)

Random MIL-STD-810G (7.7 g)
 Sinusoidal SAE J1211 (4 g)

Acceleration (operating)

MIL-STD 810G, Method 513.6
 Procedure II (16 g)

Bump IEC 60068-2-27 (10 g)

Shock MIL-STD-810G (40 g)

Immersion IEC 60529 IPX7

Compliance FCC, CE marking, Industry Canada

FEATURES

- Field upgradeable software
- 20 Hz measurement position data rate
- PAC multipath mitigating technology
- Differential GPS positioning
- Differential correction support for RTCM 2.1, 2.3, 3.0, 3.1, CMR, CMR+ and RTCA
- Navigation output support for NMEA 0183 and detailed NovAtel ASCII and binary logs
- Auxiliary strobe signals, including a configurable PPS output for time synchronization and mark inputs

NOVATEL CONNECT™

NovAtel Connect is an intuitive configuration and visualization tool allowing comprehensive control

- Easy to use wizards
- Detailed information via GUI
- Plan, view and playback files
- Remotely control and monitor
- Windows 7 platforms

INCLUDED ACCESSORIES

- Serial cable (null)
- I/O cable
- USB cable
- Automotive 12 VDC power adapter

CORRECTION SERVICES

- TerraStar-L
- TerraStar-C
- RTK ASSIST™

OPTIONAL ACCESSORIES

- GPS-700 series antennas
- ANT series antennas
- Ethernet, CAN and I/O breakout cable
- Serial cable (straight)

FIRMWARE SOLUTIONS

- ALIGN®
- GLIDE™
- RTK
- SPAN®
- RAIM
- API
- NTRIP v1.0 and v2.0
- 100 Hz output rate⁸

For the most recent details of this product:

www.novatel.com/products/gnss-receivers/enclosures/flexpak6/

novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada) or 403-295-4900

China 0086-21-68882300

Europe 44-1993-848-736

SE Asia and Australia 61-400-883-601

Version 11 Specifications subject to change without notice.

©2016 NovAtel Inc. All rights reserved.

NovAtel, OEM6, SPAN and ALIGN are registered trademarks of NovAtel Inc.

RTK ASSIST, GLIDE, FlexPak6, NovAtel CORRECT and NovAtel Connect are trademarks of NovAtel Inc.

Printed in Canada.

D15802 October 2016



1. Typical values. Performance specifications subject to GPS system characteristics, US DOD operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference sources.

2. Tracks up to 60 L1/L2 satellites.

3. The BeiDou signal is not finalized and changes in the signal structure may still occur. Designed for BeiDou Phase 3 compatibility.

4. Accuracy guaranteed only for GPS-only augmentations.

5. Requires subscription to TerraStar data service. Subscriptions available from NovAtel.

6. L2 P for GLONASS.

7. L2 C/A for GLONASS.

8. 100 Hz while tracking up to 20 satellites.

9. Typical value. No almanac or ephemerides and no approximate position or time.

10. Typical value. Almanac and recent ephemerides saved and approximate position and time entered.

11. Time accuracy does not include biases due to RF or antenna delay.

12. Export licensing restricts operation to a maximum of 515 metres per second.

13. Power consumption values for GPS L1/L2 at 6 VDC with Ethernet disabled. Power consumption may increase with other configurations.

14. User application software required.